


D35/16.P.2L spring terminal blocks

Ground with 2 connections - 16 mm 0.630 in spacing



D35/16.P.2L



16 mm 0.630 in spacing

Description

- Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact,
- Rail contact non operator dependent,
- Performances above the requirements of IEC 60947-7-2 terminal block standard,
- Secure snap on or remove from the rail.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground Screwless rail connection	Green-yellow	D35/16.P.2L	1SNA399620R1100	10	120.00

Main technical data

Connecting capacity		IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	2.5-50 mm²		
	Flexible	2.5-35 mm²		
	with non insulated ferrule			
	with insulated ferrule			
Gauge		A9		
Rated cross section		35.0 mm²		
Rated short-time withstand current (1s)		4200 A		
Protection		IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		26 mm 1.02 in
Tool		Flat screwdriver Ø 6.5 mm Ø 0.256 in

RoHS	RoHS	PG	Gost R
------	------	----	--------


Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops 12 mm 0.472 in	Grey	BADH	1SNA116900R2700	50	24.00
2 Jumper bars 2 poles 115 A	Orange	BJDL16-2	1SNA399621R0600	25	10.00
3 Terminal block markers Blank card	White	RC1010	1SNA238000R1600	1	1.30




D2.5/5.D2.L spring terminal blocks

Double deck - 5 mm 0.197 in spacing



D2.5/5.D2.L



5 mm 0.197 in spacing

Description

- Save space with double deck terminal block in just 5 mm 0.197 in spacing,
- Easy to access thanks to its front wiring entry,
- Clamping contact pressure non dependent on the operator and automatic creeping compensation,
- Numerous built-in functions: jumper system, clearly visible top marker, test sockets, etc.

Ordering details


Description	Type	Order code	Pkg qty	Weight (1 pce) g
Feed-through 2 feed-through circuits, 4 connections	Grey D2.5/5.D2.L	1SNA290161R0000	50	13.00
	Blue D2.5/5.D2.N.L	1SNA290163R0200	50	13.00

Main technical data

Connecting capacity		IEC	UL	CSA
1 conductor per clamp	Rigid - Solid / Stranded	0.12-4 mm²	26-12 AWG	26-12 AWG
	Flexible	0.12-2.5 mm²		
	with non insulated ferrule			
	with insulated ferrule			
Gauge		A2		
Rated current / Rated cross section		20 A / 2.5 mm²	20 A / 12 AWG	20 A / 12 AWG
Rated short-time withstand current (1s)		300 A		
Rated voltage		500 V	300 V	300 V
Impulse withstand voltage		6000 V		
Protection		IP20	NEMA 1	


Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		9.5 mm 0.37 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in




Notes

Mounting of the inner deck jumper bar between decks (ITVE.L).




Accessories

Description		Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1	End stops	12 mm 0.472 in	Grey BADH	1SNA116900R2700	50	24.00
2	End sections	2.5 mm 0.098 in	Grey FED5.D.L	1SNA291441R2600	20	4.20
3	Jumper bars	2 poles 24 A	Orange BJD5-2	1SNA291102R2300	50	1.00
			BJDL5-3	1SNA291103R2400	50	0.70
			BJDL5-4	1SNA291104R2500	50	0.80
			BJDL5-5	1SNA291105R2600	20	0.90
			BJDL5-10	1SNA291110R2600	20	1.20
			FC2.MC	1SNA107239R0300	20	1.00
4	Test plugs	DIA 2 mm 0.079 in	Black			
5	Inner deck jumper bars		ITVE.L	1SNA291349R1100	50	0.40
6	Terminal block markers	Blank card	White RC510	1SNA231000R0700	1	5.20




D2.5/5.T3.L spring terminal blocks

Triple deck - 5 mm 0.197 in spacing



D2.5/5.T3.L



5 mm 0.197 in spacing

Description

- Save space with triple deck terminal block in just 5 mm 0.197 in spacing,
- Easy to access thanks to its front wiring entry,
- Clamping contact pressure non dependent on the operator and automatic creeping compensation,
- Numerous built-in functions: jumper system, clearly visible top marker, test sockets, etc.

Ordering details

Description	Type	Order code	Pkg qty	Weight (1 pce) g
Feed-through 3 feed-through circuits, 6 connections	Grey ☐ D2.5/5.T3.L	1SNA290456R0000	25	20.20

Main technical data

Connecting capacity	IEC	UL	CSA
1 conductor per clamp			
Rigid - Solid / Stranded	0.14-4 mm²	24-14 AWG	24-14 AWG
Flexible with non insulated ferrule	0.14-2.5 mm²		
with insulated ferrule			
Gauge	A2		
Rated current / Rated cross section	20 A / 2.5 mm²	15 A / 14 AWG	16 A / 14 AWG
Rated short-time withstand current (1s)	300 A		
Rated voltage	500 V	150 V	150 V
Impulse withstand voltage	6000 V		
Protection	IP20	NEMA 1	

Mounting instructions



Rail		TH 35-7.5, TH 35-15
Wire stripping length		9.5 mm 0.37 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in

RoHS	RoHS	USR CNR	CSA	Gost R
------	------	---------	-----	--------

Accessories

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey ☐	BADH	1SNA116900R2700	50	24.00
2 End sections	Grey ☐	FED5.T3.L	1SNA291817R1700	20	6.60
3 Jumper bars	Orange ☐	BJDL5-2	1SNA291102R2300	50	1.00
		BJDL5-3	1SNA291103R2400	50	0.70
		BJDL5-4	1SNA291104R2500	50	0.80
		BJDL5-5	1SNA291105R2600	20	0.90
		BJDL5-10	1SNA291110R2600	20	1.20
4 Test plugs	Black ☐	FC2.MC	1SNA107239R0300	20	1.00
5 Terminal block markers	White ☐	RC510	1SNA231000R0700	1	5.20

Complete list of accessories is indicated in the terminal block datasheet.
Some accessories such as jumper bars may modify the terminal block's ratings: complete information in the accessories catalogue pages.



Ground spring terminal blocks


Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Ground	Green-yellow ☐	D2.5/5.T1.PL	1SNA290459R1300	25	25.80

D2.5/5.T3.P.L spring terminal blocks

Triple deck + ground - 5 mm 0.197 in spacing



D2.5/5.T3.P.L



5 mm 0.197 in spacing

Description

- Save space with triple deck terminal block in just 5 mm 0.197 in spacing,
- Easy to access thanks to its front wiring entry,
- Clamping contact pressure non dependent on the operator and automatic creeping compensation,
- Numerous built-in functions: jumper system, clearly visible top marker, test sockets, etc.

Ordering details

Description	Colour	Type	Order code	Pkg qty	Weight (1 pce) g
Feed-through + ground 3 feed-through circuits + 1 ground, 7 connections	Grey, Green-Yellow	D2.5/5.T3.PL	1SNA290458R1200	25	24.40


Main technical data

Connecting capacity	IEC	UL	CSA
1 conductor per clamp			
Rigid - Solid / Stranded	0.14-4 mm²	24-14 AWG	24-14 AWG
Flexible	0.14-2.5 mm²		
with non insulated ferrule			
with insulated ferrule			
Gauge	A2		
Rated current / Rated cross section	20 A / 2.5 mm²	/ 14 AWG	/ 14 AWG
Rated short-time withstand current (1s)	300 A		
Rated voltage	500 V		
Impulse withstand voltage	6000 V		
Protection	IP20	NEMA 1	

Mounting instructions

Rail		TH 35-7.5, TH 35-15
Wire stripping length		9.5 mm 0.37 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in

RoHS	UL	CSA	Gost R
------	----	-----	--------



Accessories

Description	Type	Order code	Pkg qty	Weight (1 pce) g
1 End stops	Grey	BADH	1SNA116900R2700	50 24.00
2 End sections	Grey	FED5.T3.PL	1SNA291818R2000	20 7.20
3 Jumper bars	Orange	BJDL5-2	1SNA291102R2300	50 1.00
		BJDL5-3	1SNA291103R2400	50 0.70
		BJDL5-4	1SNA291104R2500	50 0.80
		BJDL5-5	1SNA291105R2600	20 0.90
		BJDL5-10	1SNA291110R2600	20 1.20
4 Test plugs	Black	FC2.MC	1SNA107239R0300	20 1.00
5 Terminal block markers	White	RC510	1SNA231000R0700	1 5.20