

Electromechanicals relays for printed circuit board with high contacts rating and smaller than traditional automotive plug-in relays ensuring a low coil power consumption.



Relay elettromeccanici per circuito stampato con elevata portata di corrente e dimensioni ridotte rispetto ai relay plug-in automobilistici tradizionali assicurando un ridotto consumo energetico della bobina.

Typical applications in the automotive fields are:

- ABS
- Doors
- Flasher units
- Sunroof
- Power windows.

Le applicazioni tipiche nel settore automobilistico sono:

- ABS
- Porte
- Lampeggiatori di direzione
- Tettuccio
- Alzacristalli.

OUR CODE	CONTACT FORM	V	SWITCHING CURRENT (DC)	SWITCHING CURRENT (AC)	OPERATE TIME	
PCB.4117.1U	SPST	12	2x20A 28V DC	2x10A 120V AC	≤10ms	
PCB.4117.2U		24				
02.R00.10	SPDT	12	NO 20A 14V DC NC 15A 14V DC	5A 250V AC 5A 250V AC	≤10ms	
02.R00.11		24				
PCB.200.101	SPDT	12	NO 40A 14V DC NC 30A 14V DC	NO 20A 120V AC NC 20A 120V AC	≤5ms	
PCB.400.101		24				