

SEALED DIRECT WIRE FUSE AND RELAY ENCLOSURES



60 Position Fuse and Relay Enclosures

FEATURES

- Designed for 2.8 mm plug-in blade ATM type mini fuse and up to eight (8) 280 micro relay components
- Utilises sealed AMP MCP 2.8 mm receptacle terminals
- Accommodates multiple mounting configurations and brackets
- Sealed to IP67 requirements with cover installed
- For use with 14 AWG GXL - 18 AWG SXL wire
- Dual cover latches with cover position assurance capability
- 5 columns x 12 rows

ORDERING INFORMATION

Direct Wire Fuse and Relay Solutions - 60 Way Fuse Box

	Part Number
60P direct wire fuse (30x) enclosure assembly with seal and dual cover position assurance	1443997-1
60P direct wire fuse (30x) enclosure assembly with seal	1443997-2
60P direct wire fuse (30x) enclosure assembly with seal and dual cover position assurance (CPA), and mounting flange	2304643-4
Standard height cover with spare fuse holders and with top side graphic	1443996-1
Standard height cover without spare fuse holders and with top side graphic	1443996-2
Standard height cover with spare fuse holders and without top side graphic	1443996-3
Standard height cover without spare fuse holders and without top side graphic	1443996-4